



Electrical specifications

Model no.	TLALZUS4F50ABK
DLC ID	-
Power $\pm 10\%$	30W / 40W / 50W
Input voltage	AC120-347V
Frequency	50/60 Hz
Efficacy $\pm 3\%$	80 lm/W
Power factor	>0.9
Dimmable	0-10 V
Surge protection	2.5 kv
Total harmonic distortion	<20%

Product description:

- Selectable CCT and power
- Up and down lighting.
- Flicker <5%.
- Installation: suspended.
- Maximum 420W at 120V, 960W at 277V, and 1200W at 347V per circuit.
- Interconnection: maximum 7 units.
- Customizable decorative side panel options.
- Sculptural arch design with diffused, low-glare lighting.

Photometric specifications

CRI	>90
CCT	3000K / 3500K / 4000K
Beam angle	55 x 110°
Light output $\pm 3\%$	2400 lm / 3200 lm / 4000 lm

Applications:

Suitable for offices, schools, shops, showrooms, etc.

Mechanical specifications

IP rating	IP20
Material	Die cast aluminum
Lens	Polycarbonate
Net weight	5.2 kg
Product dimensions	$\pm 43.38'' \times 3.54'' \times 4.72''$ $\pm 1178 \times 90 \times 120 \text{ mm}$
Operating humidity	10% ~ 90%
Operating temperature	-25°C ~ 50°C
Lumen maintenance	-

Optional accessories

TLALZSR	TLALZSR5	TLALZPCBK	TLALZPCBK5
2 m suspension cables	5 m suspension cables	7' connection kit	5 m connection kit
TLALZLB	TLALZLBK	TLALZTBK	TLALZXBK
Straight connector	L-shaped angle connector	T-shaped angle connector	X-shaped angle connector
TLALZ4DSYE	TLALZ4DSRD	TLALZ4DSGN	TLALZ4DSBL
4' yellow decorative strip	4' red decorative strip	4' green decorative strip	4' blue decorative strip
TLALZ4DSPL			
4' purple decorative strip			