



Specifications TLARLUS4F50ABK

Electrical Specifications

Model No.	TLARLUS4F50ABK
DLC ID	N/D
Power (W) selectable ± 10%	30W / 40W / 50W
Input Voltage (V)	AC 120/347V, 50/60Hz
Efficacy ± 3%	115 lm/W
Power Factor (PF)	0.9
Surge protection	4 Kv
Total harmonic distortion	< 20%
Dimmable	0-10V

Photometric Specifications

CRI	>80
CCT selectable	3500K / 4000K / 5000K
Beam angle	120°
Light Output ± 3%	30W: 3450 lm 40W: 4600 lm
	50W: 5750 lm

Mechanical Specifications

IP Rating	IP20
Material	Aluminum + PC
Lens	Frosted
Net Weight	2.60 kg
Product size (mm)	± 1206 x 70 x 80 mm
Product size (inch)	± 47.48" x 2.75" x 3.15"
Operating Humidity	10% to 90%
Operating Temperature	-20°C to 45°C
Lumen maintenance	>82% at 100 000 hours

Accessories (not included)

TLARLSR	Suspension cables	TLARLPCBK	Suspension connecting kit (WH model illustrated)	TLARLLB	Junction support to join 2 luminaires
TLARL4SBBK	Surface installation kit (WH model illustrated)	TLARLWBCK	Wall installation kit (WH model illustrated)	TLARLUSLRF30ABK	Architectural "L" shape luminaire (Right angle)
TLARLUSLLF30ABK	Architectural "L" shape luminaire (Left angle)	TLARLUSXF60ABK	Architectural "X" shape luminaire	TLARLUSTF50ABK	Architectural "T" shape luminaire

Product description:

- Modular luminaire available in 2, 4 and 8 feet.
- Wide supply voltage supply range 120 / 347 V.
- Selectable power and CCT.
- Direct and indirect lighting.
Selectable up/down configuration : 0% up 100% down / 30% up 70% down / 50% up 50% down.
- Its versatile design makes installation easy which reduces installation time and costs.
- Savings on energy consumption compared to conventional lighting.
- Warranty: 5 years.
- Compatible with most sensors.
- 3 installation options: suspended, surface mount or wall mount, accessories not included.
- Maximum of 420W at 120V, 840W at 240V and 1200W at 347V per circuit.

Applications:

Suitable for offices, schools, shops, showrooms etc.