



Specifications TLBL3US24ADB42

Electrical Specifications

| | |
|---------------------------------|----------------------|
| Model No. | TLBL3US24ADB42 |
| DLC ID | S-8CK13A |
| Power (W) selectable $\pm 10\%$ | 14W / 19W / 24W |
| Input Voltage (V) | AC 120-347V, 50/60Hz |
| Efficacy $\pm 3\%$ | 123.4 lm/W |
| Power Factor (PF) | 0.9 |
| Surge protection | 4 Kv |
| Total harmonic distortion | $\leq 15\%$ |
| Dimmable | Non |

Photometric Specifications

| | | |
|------------------------|-----------------------|--------------|
| CRI | 72 | |
| CCT selectable | 3000K / 4000K / 5000K | |
| Beam angle | N/D | |
| Light Output $\pm 3\%$ | 14W: 1728 lm | 19W: 2345 lm |
| | 24W: 2790 lm | |

Mechanical Specifications

| | |
|-----------------------|--|
| IP Rating | IP65 |
| Material | Aluminum + PC |
| Lens | Clear |
| Net Weight | 11.9 kg |
| Product size (mm) | $\pm \text{Ø}248 \times 1\,073 \text{ mm}$ |
| Product size (inch) | $\pm \text{Ø}9.76" \times 42.24"$ |
| Operating Humidity | 10% à 90% |
| Operating Temperature | -40°C à 45°C |
| Lumen maintenance | >83% at 100 000 hours |

Product description:

- Wide supply voltage supply range 120-347V.
- Selectable power and CCT.
- Its versatile design makes installation easy which reduces installation time and costs.
- Corrosion-resistant.
- Savings on energy consumption compared to conventional lighting.
- Warranty: 5 years.
- Color: bronze.
Other colors available on request.
- Possibility of changing only the head. Other models available, not included.

Applications:

Circulation areas, building entrances, campuses, parking lots, hiking trails, etc.