



## Specifications TLBL4US24ADB42

### Electrical Specifications

Model No.	TLBL4US24ADB42
DLC ID	S-RGML3P
Power (W) selectable ± 10%	14W / 19W / 24W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	123.3 lm/W
Power Factor (PF)	0.9
Surge protection	4 Kv
Total harmonic distortion	≤15%
Dimmable	Non

### Photometric Specifications

CRI	72	
CCT selectable	3000K / 4000K / 5000K	
Beam angle	N/D	
Light Output ± 3%	14W: 1726 lm	19W: 2342 lm
	24W: 2758 lm	

### Mechanical Specifications

IP Rating	IP65
Material	Aluminum + PC
Lens	Clear
Net Weight	13.8 kg
Product size (mm)	± Ø160 x 1 048 mm
Product size (inch)	± Ø6.3" x 41.26"
Operating Humidity	10% à 90%
Operating Temperature	-40°C à 45°C
Lumen maintenance	>83% at 100 000 hours

## Product description:

- Wide supply voltage supply range 120-347V.
- Selectable power and CCT.
- Its versatile design makes installation easy which reduces installation time and costs.
- Corrosion-resistant.
- Savings on energy consumption compared to conventional lighting.
- Warranty: 5 years.
- Color: bronze.  
Other colors available on request.
- Possibility of changing only the head. Other models available, not included.

## Applications:

Circulation areas, building entrances, campuses, parking lots, hiking trails, etc.