



Specifications TLCDLUS10R32AWH

Electrical Specifications

Model No.	TLCDLUS10R32AWH
Power (W) ± 10%	20 W / 25 W / 32 W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	100 lm/W
Power Factor (PF)	>0.9
Dimmable	0-10V

Photometric Specifications

CRI	≥90
CCT	3000K / 3500K / 4000K
Beam angle	90°
Light Output ± 3%	20W: 2000 lm 25W: 2500 lm 32W: 3200 lm

Photometric Specifications

IP Rating	Damp locations
Material	Aluminum
Lens	Frosted
Net weight	N/A
Product size (mm)	± Ø279.4 x 152.4 mm
Product size (inch)	± Ø11.50" x 6.37"
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 40°C
Lumen maintenance	>73% at 100 000 hours

Product Description:

- 9.5" recessed down light.
- 235 mm (9 1/4") hole required for installation.
- BX 24" cable with connector included.
- Selectable power and CCT using a switch.
- Ultra thin 4" recessed down light.
- Color: white.

Applications:

Shopping centers, residential buildings, hotels, schools, houses, etc.

Optional accessory

