


Optional accessories



Specifications TLCDLUS4R12AWH

Electrical Specifications

Model No.	TLCDLUS4R12AWH
Power (W) ± 10%	5.5 W / 8 W / 12 W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	100 lm/W
Power Factor (PF)	>0.9
Dimmable	0-10V

Photometric Specifications

CRI	≥90
CCT	3 000 K / 3 500 K / 4 000 K
Beam angle	90°
Light Output ± 3%	5.5W: 550 lm 8W: 800 lm 12W: 1200 lm

Mechanical Specifications

IP Rating	Wet locations
Material	Aluminum
Lens	Frosted
Net Weight	408 g
Product size (mm)	± Ø151 x 109 mm
Product size (inch)	± Ø5.94" x 4.29"
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 40°C
Lumen maintenance	>71% at 100 000 hours

Product Description:

- 4" recessed down light, type IC.
- 102 mm (4") hole required for installation.
- BX 24" cable with connector included.
- Selectable power and CCT using a switch.
- Ultra thin 4" recessed down light.
- Color: white.

Possibility to customize colors using optional accessories.

Applications:

Shopping centers, residential buildings, hotels, schools, houses, etc.