



### Optional accessories



## Specifications TLCDLUS6R17AWH

### Electrical Specifications

Model No.	TLCDLUS6R17AWH
Power (W) ± 10%	7 W / 10 W / 17 W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	100 lm/W
Power Factor (PF)	>0.9
Dimmable	0-10V

### Photometric Specifications

CRI	≥90	
CCT	3 000 K / 3 500 K / 4 000 K	
Beam angle	90°	
Light Output ± 3%	7W: 700 lm	10W: 1000 lm
	17W: 1700 lm	

### Photometric Specifications

IP Rating	Damp locations
Material	Aluminum
Lens	Frosted
Net weight	598 g
Product size (mm)	± Ø203.2 x 127 mm
Product size (inch)	± Ø8.27" x 5.13"
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 40°C
Lumen maintenance	>73% at 100 000 hours

## Product Description:

- 6" recessed down light.
- 159 mm (6 1/4") hole required for installation.
- BX 24" cable with connector included.
- Selectable power and CCT using a switch.
- Ultra thin 4" recessed down light.
- Color: white.

Possibility to customize colors using optional accessories.

## Applications:

Shopping centers, residential buildings, hotels, schools, houses, etc.