



Lamp

Baffle

Trim

Optional accessories



Specifications TLCDLUS8R21AWH

Electrical Specifications

Model No.	TLCDLUS8R21AWH
Power (W) ± 10%	10 W / 15 W / 21 W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	100 lm/W
Power Factor (PF)	>0.9
Dimmable	0-10V

Photometric Specifications

CRI	≥90
CCT	3 000 K / 3 500 K / 4 000 K
Beam angle	90°
Light Output ± 3%	10W: 1000 lm 15W: 1500 lm
	21W: 2100 lm

Photometric Specifications

IP Rating	Damp locations
Material	Aluminum
Lens	Frosted
Net weight	704 g
Product size (mm)	± Ø254 x 127 mm
Product size (inch)	± Ø10.24" x 5.85"
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 40°C
Lumen maintenance	>73% at 100 000 hours

Product Description:

- 8" recessed down light.
 - 200 mm (7 7/8") hole required for installation.
 - BX 24" cable with connector included.
 - Selectable power and CCT using a switch.
 - Ultra thin 4" recessed down light.
 - Color: white.
- Possibility to customize colors using optional accessories.

Applications:

Shopping centers, residential buildings, hotels, schools, houses, etc.