



Specifications TLCYUS6R30D40ABK

Electrical specifications

Model No.	TLCYUS6R30D40ABK
Power (W) $\pm 10\%$	18 W / 24 W / 30 W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	90 lm/W
Power Factor (PF)	>0.9
Dimmable	0-10V

Photometric specifications

CRI	>90
CCT	2700K / 3000K / 3500K / 4000K / 5000K
Beam angle	40°
Light Output $\pm 3\%$	18W: 1620 lm 24W: 2160 lm 30W: 2700 lm

Mechanical specifications

IP Rating	IP65
Material	Aluminum
Lens	Glass
Net Weight	N/A
Product size (mm)	$\pm\varnothing 145 \times 242 \text{ mm}$
Product size (inch)	$\pm\varnothing 6" \times 9.53"$
Operating humidity	10% - 90%
Operating temperature	$-40^\circ\text{C} \sim 45^\circ\text{C}$
Lumen maintenance	$>77\%$ at 100 000 hours

Product description:

- Cylindrical luminaire.
- Selectable CCT and power.
- Choice of 25° or 60° lens option.
- Installation: on the surface or suspended on cord or tube.
- Tool-less twist-off cap.

Applications:

Commercial or residential indoor lighting.

Optional accessories

