



Specifications TLDL80NWH

Electrical Specifications

Model No.	TLDL80NWH
DLC ID	N/A
Power (W) ± 10%	80 W
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy ± 3%	126.64 lm/W
Power Factor (PF)	0.9056
Total harmonic distortion	<15%

Photometric Specifications

CRI	73
CCT	4 000 K
Beam angle	105°
Light Output ± 3%	10 179 lm
Dimmable	1-10V

Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminium
Lens	Clear Flat PC
Net Weight	11.6 kg
Product size (mm)	± 355.6 x 355.6 x 127 mm
Product size (inch)	± 14 x 14 x 5 in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C

Product Description:

- Die cast aluminium housing for rugged mounting and heat dissipation.
- Surface mount with quick installation kits and an aluminium plate.
- Save up in electricity consumption compared to conventional lighting fixture.
- Warranty: 5 Years.
- Compatible with most sensors.
- Other CCT available on special request.
- High voltage available on special request (347V).
- Color: white.

Applications:

Gas stations, workshops, warehouses, factories, markets, etc.
Designed for wet locations. Indoor and outdoor.