



### Electrical specifications

Model No.	TLELU2F30D120P
DLC ID	-
Power $\pm 10\%$	30 W
Input Voltage	AC120-347V
Frequency	50/60 Hz
Efficacy $\pm 10\%$	140 lm/W
Power factor	>0.95
Dimmable	0-10 V
Surge protection	10 kv
Total harmonic distortion	-

### Photometric specifications

CRI	$\geq 70$
CCT	5000 K
Beam angle	120°
Light output $\pm 10\%$	4 200 lm

### Mechanical specifications

IP Rating	IP66 / IK10
Material	Aluminum
Lens	Frosted polycarbonate
Net Weight	-
Product size	$\pm 28.35" \times 5.43" \times 4"$ $\pm 711.2 \times 127 \times 101.6 \text{ mm}$
Operating humidity	10% ~ 90%
Operating temperature	-40°C ~ 50°C
Lumen maintenance	-

### Product description:

- CLASSE 1 - DIVISION 2 - GROUPE A, B, C, D.
- UL-844 Hazardous locations
- CAN/CSA-C22.2 NO 137
- Savings on energy consumption compared to HPS / MH lighting.
- Warranty: 5 years.
- Other CCT available on request.
- Color: Gray.
- Ceiling, pole, or rail installation.
- Corrosion-resistant finish.
- 3/4" NPT cable entry.

### Applications:

Areas with risk of explosion (gas emissions), areas with vapor or dust, petrochemical complexes, mines, etc. Designed for wet locations. Indoor and outdoor.

