


### Accessories (not included)



## Specifications TLEP40P

### Electrical specifications

Model No.	TLEP20P
Power (W) ± 10%	20 W
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy ± 3%	140 lm/W
Power Factor (PF)	0.9
Total harmonic distortion	<20%
Surge protection	10 Kv

### Photometric specifications

CRI	>80
CCT	5 000 K
Beam angle	120°
Light Output ± 3%	2 800 lm

### Mechanical specifications

IP Rating	IP66
Material	Aluminum
Lens	Clear (Tempered glass)
Net Weight	4.65 kg
Product size (mm)	Ø175 x 311 mm
Product size (inch)	Ø6.9 x 12.24 in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 65°C

## Product description:

- UL 844:  
 CLASS 1 - DIVISION 1 - GROUP C, D  
 CLASS 1 - DIVISION 2 - GROUP A, B, C, D  
 CLASS 2 - DIVISION 1 - GROUP E, F, G  
 CLASS 2 - DIVISION 2 - GROUP F, G  
 CLASS 3
- Marking marine: UL1598A / UL1598 / UL844.
- Save up to 70% on electricity consumption compared to HPS/MH lighting fixture.
- Warranty: 5 years.
- Other CCT available on request.
- Color: Gray.
- 3/4" NPT.

## Applications:

Areas with risk of explosion (gas emissions), areas with vapor or dust, petrochemical complexes, mines, etc.

Designed for wet locations.  
 Indoor and outdoor.