



## Specifications TLEPEL521

### Electrical Specifications

Model No.	TLEPEL521
Consumption (W) $\pm 10\%$	10 W
Emergency consumption (W) $\pm 10\%$	7 W
Remote capacity	No
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy $\pm 3\%$	N/A
Power Factor (PF)	N/A
Emergency duration	180 minutes
Recharge time	24 hours
Operation mode	Non-maintained

### Photometric Specifications

CRI	N/A
CCT	5 000 K
Beam angle	90°
Light Output $\pm 3\%$	N/A

### Mechanical Specifications

IP Rating	NEMA 4X / IP66 / IK10
Material	Aluminum + stainless
Lens	Tempered glass
Net Weight	8 kg
Product size (mm)	$\pm 305 \times 320.5 \times 165.5$ mm
Product size (inch)	$\pm 12" \times 12.6" \times 6.5"$
Operating Humidity	10% ~ 90%
Operating Temperature	-40°C ~ 65°C
Battery	N/D
Lifespan	>50 000 hours

## Product description:

- CLASS 1 - DIVISION 1 - GROUP C, D
- CLASS 1 - DIVISION 2 - GROUP A, B, C, D
- CLASS 2 - DIVISION 1 - GROUP E, F, G
- CLASS 2 - DIVISION 2 - GROUP F, G
- CLASS 3
- CAN / CSA-C22.2 NO. 137
- UL-844 Hazardous locations
- UL-924 Emergency lighting
- UL-1598A Marine outdoor
- UL-1598 Damp locations
- UL-8750 LED security
- 2 adjustable lighting heads from 0° to 180°.
- Wall installation.

## Applications:

Explosion-proof emergency lighting.