



Specifications TLEPEL522

Electrical Specifications

| | |
|--------------------------------|---------------------|
| Model No. | TLEPEL522 |
| Consumption (W) ±10% | 10 W |
| Emergency consumption (W) ±10% | 5 W |
| Remote capacity | No |
| Input Voltage (V) | AC100-277V, 50/60Hz |
| Efficacy ± 3% | N/A |
| Power Factor (PF) | N/A |
| Emergency duration | 180 minutes |
| Recharge time | 24 hours |
| Operation mode | Non-maintained |

Photometric Specifications

| | |
|-------------------|---------|
| CRI | N/A |
| CCT | 5 000 K |
| Beam angle | 90° |
| Light Output ± 3% | 500 lm |

Mechanical Specifications

| | |
|-----------------------|------------------------|
| IP Rating | NEMA 4X / IP66 / IK10 |
| Material | Aluminum + stainless |
| Lens | Tempered glass |
| Net Weight | 20 kg |
| Product size (mm) | ± 546 x 430 x 159 mm |
| Product size (inch) | ± 21.5" x 16.9" x 6.2" |
| Operating Humidity | 10% ~ 90% |
| Operating Temperature | -40°C ~ 65°C |
| Battery | N/D |
| Lifespan | >50 000 hours |

Product description:

- CLASS 1 - DIVISION 1 - GROUP C, D
- CLASS 1 - DIVISION 2 - GROUP A, B, C, D
- CLASS 2 - DIVISION 1 - GROUP E, F, G
- CLASS 2 - DIVISION 2 - GROUP F, G
- CLASS 3
- CAN / CSA-C22.2 NO. 137
- UL-844 Hazardous locations
- UL-924 Emergency lighting
- UL-1598A Marine outdoor
- UL-1598 Damp locations
- UL-8750 LED security
- 2 adjustable lighting heads from 0° to 180°.
- Wall installation.

Applications:

Explosion-proof emergency lighting.