



Specifications TLEPES522

Electrical Specifications

Model No.	TLEPES522
Consumption (W) ±10%	10 W
Emergency consumption (W) ±10%	5 W
Remote capacity	No
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy ± 3%	N/A
Power Factor (PF)	N/A
Emergency duration	180 minutes
Recharge time	24 hours
Operation mode	Maintained for the sign Non-maintained for the lighting heads

Photometric Specifications

CRI	N/A
CCT	5 000 K
Beam angle	90°
Light Output ± 3%	500 lm

Mechanical Specifications

IP Rating	NEMA 4X / IP66 / IK10
Material	Aluminum + stainless
Lens	Tempered glass
Net Weight	25 kg
Product size (mm)	± 546 x 648 x 159 mm
Product size (inch)	± 21.5" x 25.5" x 6.2"
Operating Humidity	10% ~ 90%
Operating Temperature	-40°C ~ 65°C
Battery	N/D
Lifespan	>50 000 hours

Product description:

- CLASS 1 - DIVISION 1 - GROUP C, D
- CLASS 1 - DIVISION 2 - GROUP A, B, C, D
- CLASS 2 - DIVISION 1 - GROUP E, F, G
- CLASS 2 - DIVISION 2 - GROUP F, G
- CLASS 3
- CAN / CSA-C22.2 NO. 137
- UL-844 Hazardous locations
- UL-924 Emergency lighting
- UL-1598A Marine outdoor
- UL-1598 Damp locations
- UL-8750 LED security
- 2 adjustable lighting heads from 0° to 180°.
- Wall installation.

Applications:

Explosion-proof emergency lighting.

