



Specifications TLESBU275T2

Electrical Specifications

| | |
|--------------------------------|---|
| Model No. | TLESBU275T2 |
| Consumption (W) ±10% | 21 W |
| Emergency consumption (W) ±10% | 10 W (2 x 5 W) |
| Emergency duration | 12 V, 75 W : 120 min 12 V, 97 W : 90 min 12 V, 275 W : 30 min |
| Input Voltage (V) | AC120 / 277 / 347V, 50/60Hz |
| Efficacy ± 3% | 75 lm/W |
| Power Factor (PF) | 0.8 |
| Recharge time | 45 hours |
| Operation mode | Non-maintained |

Photometric Specifications

| | |
|-------------------|---------|
| CRI | 85 |
| CCT | 6 500 K |
| Beam angle | 40° |
| Light Output ± 3% | 750 lm |

Mechanical Specifications

| | |
|-----------------------|-------------------------|
| IP Rating | Damp locations |
| Material | Metal + ABS |
| Lens | PC |
| Net Weight | N/D |
| Product size (mm) | ± 388 x 348 x 107 mm |
| Product size (inch) | ± 15.3" x 13.7" x 4.2" |
| Operating Humidity | 10% ~ 90% |
| Operating Temperature | 15°C ~ 35°C |
| Battery | Lead Acid 2 x 12V, 12Ah |
| Battery warranty | 2 years |

Product description:

- 275 W battery unit with 2 lighting heads.
- Overload and over-discharge protection.
- Test button and power indicator included.
- Adjustable lighting heads.
- Additional light heads can be connected remotely.

Applications:

Indoor battery unit and emergency lighting.