



#### Electrical specifications

Model No.	TLESBU320T2
Consumption (W) $\pm 10\%$	46 W - 63 W
Emergency consumption (W) $\pm 10\%$	10 W (2 x 5 W)
Emergency duration	24 V, 80 W : 120 min
	24 V, 106 W : 90 min
	24 V, 160 W : 60 min
	24 V, 320 W : 30 min
Input voltage (V)	120/347 V, 50/60 Hz
Efficacy $\pm 3\%$	75 lm/W
Power factor	0.8
Recharge time	50 hours
Operation mode	No-maintained

#### Photometric specifications

CRI	85
CCT	6500K
Beam angle	30°
Light output $\pm 3\%$	750 lm

#### Mechanical specifications

IP rating	IP20
Material	Steel (battery) ABS (head)
Lens	Polycarbonate
Net weight	16.6 kg
Product dimensions	$\pm 16.38'' \times 16.77'' \times 3.66''$
	$\pm 416 \times 426 \times 93 \text{ mm}$
Operating temperature	15°C ~ 35°C
Battery	Lead acide 12 V 18 AH x 2
Battery warranty	2 years

#### Product description:

- 320W battery unit with two lighting heads.
- Complies with standard: CSA 22.2#141-15.
- Meets ICES-005 requirements.
- Overload and over-discharge protection.
- 1500V surge protection.
- Test button and power indicator included.
- Adjustable lighting heads.
- Additional light heads can be connected remotely.

#### Applications:

Indoor battery unit and emergency lighting.