



## Specifications TLESBU72T2

### Electrical Specifications

Model No.	TLESBU72T2
Consumption (W) $\pm 10\%$	15 W
Emergency consumption (W) $\pm 10\%$	4 W
Remote capacity	12 V, 22 W : 120 min 12 V, 27 W : 90 min 12 V, 72 W : 30 min
Input Voltage (V)	AC120 / 277 / 347V, 50/60Hz
Efficacy $\pm 3\%$	65 lm/W
Power Factor (PF)	N/D
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Non-maintained

### Photometric Specifications

CRI	N/D
CCT	6 500 K
Beam angle	40°
Light Output $\pm 3\%$	260 lm

### Mechanical Specifications

IP Rating	Damp locations
Material	Metal + ABS
Lens	PC
Net Weight	N/D
Product size (mm)	$\pm 355 \times 338 \times 88$ mm
Product size (inch)	$\pm 13.98" \times 13.31" \times 3.46"$
Operating Humidity	10% à 90%
Operating Temperature	10°C ~ 40°C
Battery	Lead Acid 12V, 7Ah
Battery warranty	2 years

## Product description:

- 72 W battery unit with 2 lighting heads.
- Overload and over-discharge protection.
- Test button and power indicator included.
- Adjustable lighting heads.
- Additional light heads can be connected remotely.

## Applications:

Indoor battery unit and emergency lighting.