



## Specifications TLESMBU36T2-BK

### Electrical Specifications

Model No.	TLESMBU36T2-BK
Consumption (W) $\pm 10\%$	3.5 - 7.5 W
Emergency consumption (W) $\pm 10\%$	1 W + 2 x 2 W
Remote capacity	6 V, 9 W : 120 min 6 V, 12 W : 90 min 6 V, 36 W : 30 min
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy $\pm 3\%$	52.5 lm/W
Power Factor (PF)	N/A
Emergency duration	>30 minutes at 36 W
Recharge time	24 hours
Operation mode	No

### Photometric Specifications

CRI	85
CCT	6 000 K ~ 6 500 K
Beam angle	40°
Light Output $\pm 3\%$	210 lm (105 lm each head)

### Mechanical Specifications

IP Rating	Damp locations
Material	Metal + ABS
Lens	PC
Net Weight	N/A
Product size (mm)	$\pm 322 \times 280 \times 152$ mm
Product size (inch)	$\pm 12.7" \times 11" \times 6"$
Operating Humidity	90%
Operating Temperature	5°C ~ 30°C
Battery	Lead Acid 6V, 6Ah
Battery warranty	2 years

## Product description:

- 36 W battery unit with 2 lighting heads.
- Overload and over-discharge protection.
- Test button and power indicator included.
- Adjustable lighting heads.
- Additional light heads can be connected remotely.

## Applications:

Indoor battery unit and emergency lighting.