



Specifications TLESMU01-BK

Electrical Specifications

Model No.	TLESMU01-BK
Consumption (W) $\pm 10\%$	3 ~ 4 W
Emergency consumption (W) $\pm 10\%$	1 W
Remote capacity	No
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	N/A
Power Factor (PF)	N/A
Emergency duration	> 120 minutes
Recharge time	24 hours
Operation mode	Maintained

Photometric Specifications

CRI	85
CCT	6 000 K ~ 6 500 K
Beam angle	N/A
Light Output $\pm 3\%$	N/A

Mechanical Specifications

IP Rating	Damp locations
Material	Metal
Lens	N/A
Net Weight	N/A
Product size (mm)	$\pm 310 \times 192 \times 54$ mm
Product size (inch)	$\pm 12.2" \times 7.6" \times 2.13"$
Operating Humidity	90%
Operating Temperature	5°C ~ 30°C
Battery	Ni-Cd 3.6V, 1000 mAh
Battery warranty	2 years

Product description:

- Exit sign.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Powder-coated metal frame.
- Test button and power indicator included.
- Universal mounting: wall, ceiling, flag.

Applications:

Indoor exit sign.



info@technilight.ca

WWW.TECHNILIGHT.CA