



Specifications TLESMU21

Electrical Specifications

Model No.	TLESMU21
Consumption (W) ±10%	4 W
Emergency consumption (W) ±10%	1.8 W
Remote capacity	No
Input Voltage (V)	AC120 / 347V, 50/60Hz
Efficacy ± 3%	≥25 lm/W
Power Factor (PF)	N/D
Emergency duration	90 minutes
Recharge time	24 hours
Operation mode	Maintained for the sign Non-maintained for the lighting heads

Photometric Specifications

CRI	N/D
CCT	6 500 K
Beam angle	80°
Light Output ± 3%	≥100 lm

Mechanical Specifications

IP Rating	Damp locations
Material	Metal + ABS
Lens	PC
Net Weight	N/D
Product size (mm)	± 330 x 312 x 56 mm
Product size (inch)	± 13" x 12.3" x 2.2"
Operating Humidity	10% à 90%
Operating Temperature	0°C ~ 40°C
Battery	Ni-Cd 3.6V, 1200mAh
Battery warranty	2 years

Product description:

- Exit sign with 2 lighting heads.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Powder-coated metal frame.
- Test button and power indicator included.
- Universal mounting: wall, ceiling, flag.

Applications:

Indoor exit sign and emergency lighting.

