



Specifications TLESPU01

Electrical Specifications

Model No.	TLESPU01
Consumption (W) ±10%	4.5 W
Emergency consumption (W) ±10%	1 W
Remote capacity	3.6V : 4.8 W
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy ± 3%	N/D
Power Factor (PF)	N/D
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Maintained

Photometric Specifications

CRI	N/D
CCT	6 500 K
Beam angle	N/D
Light Output ± 3%	N/D

Mechanical Specifications

IP Rating	Damp locations
Material	Thermoplastic ABS
Lens	N/D
Net Weight	N/D
Product size (mm)	± 345 x 230 x 59 mm
Product size (inch)	± 13.6" x 9.06" x 2.32"
Operating Humidity	10% ~ 90%
Operating Temperature	0°C ~ 40°C
Battery	Ni-Cd 3.6V, 900mAh
Battery warranty	2 years

Product description:

- Exit sign.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Injection-molded ABS thermoplastic case.
- Test button and power indicator included.
- Universal mounting: wall, ceiling, flag.
- Additional light heads can be connected remotely.

Applications:

Indoor exit sign.

