



Specifications TLESPU21

Electrical Specifications

Model No.	TLESPU21
Consumption (W) ±10%	4.5 W
Emergency consumption (W) ±10%	3 W
Remote capacity	3.6V : 4.8 W
Input Voltage (V)	AC120 / 347V, 50/60Hz
Efficacy ± 3%	60 lm/W
Power Factor (PF)	N/D
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Maintained for the sign Non-maintained for the lighting heads

Photometric Specifications

CRI	N/D
CCT	6 500 K
Beam angle	25°
Light Output ± 3%	120 lm

Mechanical Specifications

IP Rating	Damp locations
Material	Thermoplastic ABS
Lens	PC
Net Weight	N/D
Product size (mm)	± 345 x 285 x 59 mm
Product size (inch)	± 13.6" x 11.22" x 2.32"
Operating Humidity	10% ~ 90%
Operating Temperature	0°C ~ 40°C
Battery	Ni-Cd 3.6V, 3600mAh
Battery warranty	2 years

Product description:

- Exit sign with 2 lighting heads.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Injection-molded ABS thermoplastic housing.
- Test button and power indicator included.
- Universal mounting: wall, ceiling, flag.
- Additional light heads can be connected remotely.

Applications:

Indoor exit sign and emergency lighting.

