



## Specifications TLESWU01-BK

### Electrical Specifications

Model No.	TLESWU01-BK
Consumption (W) $\pm 10\%$	4.5 W
Emergency consumption (W) $\pm 10\%$	1 W
Remote capacity	No
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	N/D
Power Factor (PF)	N/D
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Maintained

### Photometric Specifications

CRI	N/D
CCT	6 500 K
Beam angle	N/D
Light Output $\pm 3\%$	N/D

### Mechanical Specifications

IP Rating	IP65 / NEMA4X
Material	Thermoplastic ABS
Lens	N/D
Net Weight	N/D
Product size (mm)	$\pm 354 \times 232 \times 76$ mm
Product size (inch)	$\pm 13.94" \times 9.13" \times 2.99"$
Operating Humidity	10% ~ 90%
Operating Temperature	-20°C ~ 40°C
Battery	Ni-Mh 3.6V, 1500mAh
Battery warranty	2 years

## Product description:

- Exit sign.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Injection-molded ABS thermoplastic case.
- Test button and power indicator included.
- Universal wall mounting.

## Applications:

Exit sign for wet locations.



[info@technilight.ca](mailto:info@technilight.ca)

**WWW.TECHNILIGHT.CA**