



### Specifications TLESWU01

#### Electrical Specifications

Model No.	TLESWU01
Consumption (W) ±10%	4.5 W
Emergency consumption (W) ±10%	1 W
Remote capacity	No
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy ± 3%	N/D
Power Factor (PF)	N/D
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Maintained

#### Photometric Specifications

CRI	N/D
CCT	6 500 K
Beam angle	N/D
Light Output ± 3%	N/D

#### Mechanical Specifications

IP Rating	IP65 / NEMA4X
Material	Thermoplastic ABS
Lens	N/D
Net Weight	N/D
Product size (mm)	± 354 x 232 x 76 mm
Product size (inch)	± 13.94" x 9.13" x 2.99"
Operating Humidity	10% ~ 90%
Operating Temperature	-20°C ~ 40°C
Battery	Ni-Mh 3.6V, 1500mAh
Battery warranty	2 years

### Product description:

- Exit sign.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Injection-molded ABS thermoplastic case.
- Test button and power indicator included.
- Universal wall mounting.

### Applications:

Exit sign for wet locations.

