



## Specifications TLESWU21-BK

### Electrical Specifications

Model No.	TLESWU21-BK
Consumption (W) $\pm 10\%$	4.5 W
Emergency consumption (W) $\pm 10\%$	1 W (2 x 0.5 W)
Remote capacity	No
Input Voltage (V)	AC 120 / 347V, 50/60Hz
Efficacy $\pm 3\%$	134 lm/W
Power Factor (PF)	0.8
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Maintained for the sign Non-maintained for the lighting heads

### Photometric Specifications

CRI	85
CCT	6 500 K
Beam angle	25°
Light Output $\pm 3\%$	134 lm

### Mechanical Specifications

IP Rating	IP65 / NEMA4X
Material	Thermoplastic ABS
Lens	PC
Net Weight	N/D
Product size (mm)	$\pm 354 \times 370 \times 76$ mm
Product size (inch)	$\pm 13.94" \times 14.57" \times 2.99"$
Operating Humidity	10% ~ 90%
Operating Temperature	-25°C ~ 40°C
Battery	Ni-Mh 3.6V, 2500mAh
Battery warranty	2 years



## Product description:

- Exit sign with 2 lighting heads.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Injection-molded ABS thermoplastic housing.
- Test button and power indicator included.
- Universal wall mounting.

## Applications:

Exit sign and emergency lighting for wet locations.



[info@technilight.ca](mailto:info@technilight.ca)

**WWW.TECHNILIGHT.CA**