



Specifications TLESWU21

Electrical Specifications

Model No.	TLESWU21
Consumption (W) ±10%	4.5 W
Emergency consumption (W) ±10%	1 W (2 x 0.5 W)
Remote capacity	No
Input Voltage (V)	AC120 / 347V, 50/60Hz
Efficacy ± 3%	134 lm/W
Power Factor (PF)	0.8
Emergency duration	120 minutes
Recharge time	24 hours
Operation mode	Maintained for the sign Non-maintained for the lighting heads

Photometric Specifications

CRI	85
CCT	6 500 K
Beam angle	25°
Light Output ± 3%	134 lm

Mechanical Specifications

IP Rating	IP65 / NEMA4X
Material	Thermoplastic ABS
Lens	PC
Net Weight	N/D
Product size (mm)	± 354 x 370 x 76 mm
Product size (inch)	± 13.94" x 14.57" x 2.99"
Operating Humidity	10% ~ 90%
Operating Temperature	-25°C ~ 40°C
Battery	Ni-Mh 3.6V, 2500mAh
Battery warranty	2 years

Product description:

- Exit sign with 2 lighting heads.
- Single- or double-sided with editable captions.
- Overload and over-discharge protection.
- Injection-molded ABS thermoplastic housing.
- Test button and power indicator included.
- Universal wall mounting.

Applications:

Exit sign and emergency lighting for wet locations.

