



## Specifications TLFE200HC120P

### Electrical Specifications

Model No.	TLFE200HC120P
DLC ID	N/A
Power (W) ± 10%	200 W
Input Voltage (V)	AC200-480V, 50/60Hz
Efficacy ± 3%	146 lm/W
Power Factor (PF)	0.9
Total harmonic distortion	≤20%

### Photometric Specifications

CRI	83
CCT	5 000 K
Beam angle	120°
Light Output ± 3%	29 200 lm
Dimmable	0-10 V

### Mechanical Specifications

IP Rating	IP66
Material	Aluminum
Lens	Clear Tempered Glass
Net Weight	8.3 kg
Product size (mm)	± 380 x 230 x 188 mm
Product size (inch)	± 14.96 x 9.06 x 7.41 in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 40°C

## Product Description:

- UL 844:
  - CLASS 1 - DIVISION 2 - GROUP A, B, C, D
  - CLASS 2 - DIVISION 1 - GROUP E, F, G
  - CLASS 2 - DIVISION 2 - GROUP F, G
  - CLASS 3
- Marine marking: UL 1598A
- Saves up to 70% on electricity consumption compared to HPS/MH lighting fixture.
- Warranty: 5 Years.
- 4 000 K and 5 700 K available on special request.
- Color: gray.
- Wall mount or ceiling mount bracket.

## Applications:

Areas with risk of explosion (gas emissions), areas with vapor or dust, petrochemical complexes, mines, etc.

Designed for wet locations.

Indoor and outdoor.