



## Specifications TLFLF15SWPBK

### Electrical Specifications

Model No.	TLFLF15SWPBK
DLC ID	N/A
Power (W) ± 10%	15 W
Input Voltage (V)	AC 120/277V, 50/60Hz
Efficacy ± 3%	120 lm/W
Power Factor (PF)	0.8994
Total harmonic distortion	<15%

### Photometric Specifications

CRI	71.2
CCT	5 000 K
Beam angle	80° x 110°
Light Output ± 3%	1 800 lm
Dimmable	No

### Mechanical Specifications

IP Rating	IP65
Material	Die cast aluminum
Lens	Polycarbonate
Net Weight	1 kg
Product size (mm)	± 127 x 152 x 46 mm
Product size (inch)	± 5.1 x 6.1 x 1.8 in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 45°C
Lifespan (L70)	72 000 hours

## Product Description:

- Mounting option: SW ("Knuckle" bracket) NPT 1/2 in.
- 2 mounting options available. (SW and TU)
- Built with materials that have low thermal expansion. Stays waterproof above -40°C.
- Save on electricity consumption compared to standard lighting fixture.
- Color: black.
- Warranty: 5 Years.
- 18" power cord.

## Applications:

Designed for use in wet locations.  
Flood luminaire.