

Selectable power and CCT


**Specifications TLFLGUS150TUABK**
**Electrical Specifications**

Model No.	TLFLGUS150TUABK
DLC ID	S-3ISF0W
Selectable power (W) ± 10%	80 W / 100 W / 150 W
Input Voltage (V)	AC 100-347V, 50/60Hz
Efficacy ± 3%	135 lm/W
Power Factor (PF)	0.95
Total harmonic distortion	≤15%
Replace MH/HPS	150 W / 250 W / 400 W

**Photometric Specifications**

CRI	70	
Selectable CCT	3 000 K / 4 000 K / 5 000 K	
Beam angle	120°	
Light Output ± 3%	80W: 10 800 lm	100W: 13 500 lm
	150W: 20 250 lm	
Dimmable	0-10 V	

**Mechanical Specifications**


IP Rating	IP66
Material	Aluminum
Lens	Tempered glass
Net Weight	3.5 kg
Product size (mm)	± 338.5 x 323 x 80 mm
Product size (inch)	± 13.3 x 12.7 x 3.15 in
Operating Humidity	15% to 95%
Operating Temperature	-30°C to 45°C
Lumen maintenance	>75% at 100 000 hours

**Product Description:**

- Bracket: TU ("U" bracket) included.
- SF bracket available, optional only.
- Selectable power and CCT with a switch.
- Saves on electricity consumption compared to standard lighting fixture.
- Color: black.
- Warranty: 5 Years.
- 18" power cord.

**Applications:**

Designed for use in wet locations.  
Flood luminaire.

**Optional**

**TLFLGSFBK**  
SF bracket