

Selectable power and CCT



Specifications TLGNAS30ABK

Electrical Specifications

Model No.	TLGNAS30ABK	
DLC ID	N/D	
Power (W) ±10%	15W / 20W / 30W	
Input Voltage (V)	AC 120 V, 50/60Hz	
Efficacy ± 3%	95 lm/W	
Power Factor	>0.9	
Surge protection	N/D	
Total harmonic distortion	<15%	
Dimmable	No	

Photometric Specifications

CRI	70	
CCT selectable	3000K / 4000K / 5000K	
Beam angle	100°	
Light output ± 3%	15W: 1425 lm	20W: 1900 lm
	30W: 2850 lm	

Mechanical Specifications


IP Rating	IP65
Material	Aluminum + PC
Lens	Clear
Net Weight	2.1 kg
Product size (mm)	± 587 x 246 x 350 mm
Product size (inch)	± 23.1" x 9.7" x 13.8"
Operating humidity	10% ~ 90%
Operating temperature	-40°C ~ 40°C
Lifespan (L70)	50 000 hours

Product description:

- Selectable power and CCT.
- Built-in photocell.
- Wall installation.
- Adjustable installation bracket included.
- Waterproof and dustproof.
- Saves in electricity consumption compared to MH and HPS lighting fixture.
- Warranty: 5 Years.

Applications:

Suitable for gardens, yards, patios, driveways, garages, barns, farms, carports, loading zones, building exteriors, parking lots, streets, storefront lighting stores and many others outdoor spaces.



Height	Aver. lux	Diameter
1m	1641 lx	223cm
2m	410 lx	447cm
3m	182 lx	670cm
4m	102 lx	893cm
5m	65 lx	1117cm