



Specifications TLHBE200HF120P

Electrical Specifications

Model No.	TLHBE200HF120P
DLC ID	N/D
Power (W) ± 10%	200 W
Input Voltage (V)	AC200-480V, 50/60Hz
Efficacy ± 3%	130 lm/W
Power Factor (PF)	0.9
Total harmonic distortion	≤20%

Photometric Specifications

CRI	>80
CCT	5 000 K
Beam angle	120°
Light Output ± 3%	26 000 lm
Dimmable	0-10 V

Mechanical Specifications

IP Rating	IP66
Material	Aluminum
Lens	Frosted Tempered Glass
Net Weight	N/A
Product size (mm)	± Ø370 x 374 mm
Product size (inch)	± Ø14.57" x 14.72"
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 40°C



Accessories (not included)

<p>EX-HD51-KB1-3/4NPT Junction box</p>	<p>EX-HD51-KYD-90-3/4NPT 90° bracket</p>	<p>EX-HD51-KYD-45-3/4NPT 45° bracket</p>
---	---	---

Product Description:

- UL 844: hazardous locations
CAN / CSA-C22.2 NO. 137
- CLASS 1 - DIVISION 2 - GROUP A, B, C, D
- CLASS 2 - DIVISION 1 - GROUP E, F, G
- CLASS 2 - DIVISION 2 - GROUP F, G
- CLASS 3
- Marine marking: UL 1598A
- Save up to 70% on electricity consumption compared to HPS/MH lighting fixture.
- Warranty: 5 Years.
- Other CCT available on special request.
- Color: gray.
- Wall mount or ceiling mount bracket.

Applications:

Areas with risk of explosion (gas emissions), areas with vapor or dust, petrochemical complexes, mines, etc.

Designed for wet locations.
Indoor and outdoor.