




TLLAU200T4BBK IP65 / NEMA 4X

Parking and wide area



Specifications TLLAU200T4BBK

Electrical Specifications

Model No.	TLLAU200T4BBK
DLC ID	N/A
Power (W) ± 10%	200 W
Input Voltage (V)	120-347V, 50/60Hz
Efficacy ± 3%	110 lm/W
Power Factor (PF)	0.891
Dimmable	0-10V
Replace MH/HPS	575 W
Surge protection	6 kv
Total harmonic distortion	≤15%

Photometric Specifications

CRI	≥70
CCT	2 200 K
Beam angle	Type IV Medium
Light Output ± 3%	22 000 lm
BUG rating	B3-U0-G5

Mechanical Specifications

IP Rating	IP65 / NEMA 4X
Material	Aluminum
Lens	PC
Net Weight	6.5 kg
Product size (mm)	± 579 x 389 x 87 mm
Product size (inch)	± 22.8 x 15.3 x 3.4 in
EPA	2.39 ft ²
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 45°C
Lumen maintenance	N/A

Optional accessories available



Product Description:

- Light and slim housing.
- Optional photocell. Installation on top of the luminaire. Drilling required.
- Optional motion sensor.
- Easily replace traditional MH or HPS luminaire fixture.
- Powerful light efficacy.
- Save in electricity consumption compared to fluorescent lighting fixture.
- Other CCT available on special request.
- Color: Black.
Other colors available on special request.
- Warranty: 5 Years.

Applications:

Outdoor parking and wide area.

info@technilight.ca

WWW.TECHNILIGHT.CA