


Parking and wide area



Optional accessories available



Specifications TLLAU75T4BBK

Electrical Specifications

Model No.	TLLAU75T4BBK
DLC ID	N/A
Power (W) $\pm 10\%$	75 W
Input Voltage (V)	120-347V, 50/60Hz
Efficacy $\pm 3\%$	110 lm/W
Power Factor (PF)	0.889
Dimmable	0-10V
Replace MH/HPS	200 W
Surge protection	6 kv
Total harmonic distortion	$\leq 20\%$

Photometric Specifications

CRI	≥ 70
CCT	2 200 K
Beam angle	Type IV Medium
Light Output $\pm 3\%$	8 250 lm
BUG rating	B3-U0-G5

Mechanical Specifications

IP Rating	IP65 / NEMA 4X
Material	Aluminum
Lens	PC
Net Weight	5 kg
Product size (mm)	$\pm 488 \times 293 \times 87$ mm
Product size (inch)	$\pm 19.2 \times 11.5 \times 3.4$ in
EPA	1.92 ft ²
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 45°C
Lumen maintenance	N/A

Product Description:

- Light and slim housing.
- Optional photocell. Installation on top of the luminaire. Drilling required.
- Optional motion sensor.
- Easily replace traditional MH or HPS luminaire fixture.
- Powerful light efficacy.
- Save in electricity consumption compared to fluorescent lighting fixture.
- Other CCT available on special request.
- Color: Black. Other colors available on special request.
- Warranty: 5 Years.

Applications:

Outdoor parking and wide area.

info@technilight.ca

WWW.TECHNILIGHT.CA