



Specifications TLLSUS8F80AD

Electrical Specifications

Model No.	TLLSUS8F80AD
DLC ID	N/A
Power (W) selectable $\pm 10\%$	60W / 70W / 80W
Input Voltage (V)	AC 120/347V, 50/60Hz
Efficacy $\pm 3\%$	130 lm/W
Power Factor (PF)	>0.9
Surge protection	N/A
Total harmonic distortion	N/A

Photometric Specifications

CRI	≥ 80
CCT selectable	3500K / 4000K / 5000K
Beam angle	120°
Light Output $\pm 3\%$	60W: 7800 lm 70W: 9100 lm 80W: 10400 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP20
Material	Steel + PC
Lens	Frosted
Net Weight	N/A
Product size (mm)	$\pm 2438 \times 76 \times 68$ mm
Product size (inch)	$\pm 95.98" \times 3" \times 2.68"$
Operating Humidity	10% - 90%
Operating Temperature	-25°C ~ 40°C
Lifespan (L70)	N/A

Product Description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Easy Installation with fast connection design, shorten the installation process and save labor cost.
- Save up in electricity consumption compared to fluorescent lighting fixture.
- Warranty: 5 years.
- It could be fitted with sensor.
- Ceiling installation or optional suspension kit, not included.
- Optional protective grid, not included.

Applications:

Suitable for houses, basements, warehouses, garages, shops, etc.

Optional accessory



TLSSR
Suspension kit