



RoHS



Specifications TLPTMUS60ABK

Electrical Specifications

| | |
|---------------------------------|----------------------|
| Model No. | TLPTMUS60ABK |
| DLC ID | N/D |
| Power (W) selectable $\pm 10\%$ | 30 W / 50 W / 60 W |
| Input Voltage (V) | AC 120-347V, 50/60Hz |
| Efficacy $\pm 3\%$ | 105 lm/W |
| Power Factor (PF) | 0.9 |
| Dimmable | No |
| Surge protection | N/A |
| Total harmonic distortion | $\leq 20\%$ |

Photometric Specifications

| | |
|------------------------|-----------------------------|
| CRI | >70 |
| CCT selectable | 3 000 K / 4 000 K / 5 000 K |
| Beam angle | 180° |
| Light Output $\pm 3\%$ | Min: 3 150 lm Max: 6 300 lm |

Mechanical Specifications

| | |
|-----------------------|---|
| IP Rating | IP65 |
| Material | Aluminum + PC |
| Lens | Type V |
| Net Weight | 6.2 kg |
| Product size (mm) | $\pm \text{Ø}450 \times 865 \text{ mm}$ |
| Product size (inch) | $\pm \text{Ø}17.7" \times 34.1"$ |
| Operating Humidity | 10% - 90% |
| Operating Temperature | -40°C ~ 45°C |
| Lumen maintenance | >86% at 100 000 hours |

Product description:

- Wide supply voltage supply range 120-347 V.
- Selectable power and CCT.
- Savings on energy compared to conventional lighting.
- Color: black.
Other colors available on order with minimum quantity.
- Warranty: 5 years.

Applications:

Suitable for parks, bike paths, sidewalks, etc.