



## Specifications TLQLC30P

### Electrical Specifications

Model No.	TLQLC30P
Power (W) $\pm 10\%$	30 W
Input Voltage (V)	120 V, 50-60 Hz
Efficacy $\pm 3\%$	110 lm/W
Power Factor (PF)	>0.9

### Photometric Specifications

CRI	70
CCT	5 000 K
Beam angle	30°
Light Output $\pm 3\%$	3 300 lm

### Mechanical Specifications

IP Rating	IP65
Material	Die Cast Aluminium
Lens	Clear
Net Weight	5.9 kg
Product size (mm)	$\pm \varnothing 140 \times 107.5$ mm
Product size (inch)	$\pm \varnothing 5.51" \times 4.21"$
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 50°C
Lumen maintenance	>82% at 100 000 hours

## Product Description:

- Clear glass lens with die cast aluminium housing, rated for wet location.
- Save in electricity consumption compared to fluorescent lighting fixture.
- No bulb replacement required.
- Instant start-up at full output even in cold temperatures.
- Easy installation.
- Yellow powder-coat finish for maximum visibility.
- Low heat.

## Applications:

Shipping and receiving loading docks, inspection stations, general work lighting, indoor and outdoor, spot lighting, etc.