



## Specifications TLSD13R24AWH

### Electrical Specifications

Model No.	TLSD13R24AWH
Power (W) ± 10%	24 W
Input Voltage (V)	AC120 V, 60Hz
Efficacy ± 3%	85 lm/W
Power Factor (PF)	>0.9
Dimmable	Triac

### Photometric Specifications

CRI	90	
CCT	2700K / 3000K / 3500K / 4000K / 5000K	
Beam angle	120°	
Light Output ± 3%	2700K: 1872 lm	3000K: 1974 lm
	3500K: 2092 lm	4000K: 2134 lm
	5000K: 2109 lm	

### Mechanical Specifications

IP Rating	Damp locations
Material	Aluminum + PS
Lens	Frosted
Net Weight	N/A
Product size (mm)	± Ø325 x 25 mm
Product size (inch)	± Ø12.8" x 0.98"
Operating Humidity	10% - 90%
Operating Temperature	-25°C ~ 45°C
Lifespan (L70)	>50 000 hours

## Product description:

- 13" thin LED surface fixture.
- Built-in driver. Save space.
- Selectable CCT.
- Can be use as main or decorative lighting.
- Luminaire color: white.
- Choice of the frame (color): black or brushed nickel.

## Applications:

Offices, shopping malls, schools, hotels, homes, etc.

### Optionnal frames

