



Specifications TLSD4R10ASWH

Electrical Specifications

Model No.	TLSD4R10ASWH
Power (W) \pm 10%	10 W
Input Voltage (V)	AC120 V, 60Hz
Efficacy \pm 3%	60 lm/W
Power Factor (PF)	>0.9
Dimmable	Triac

Photometric Specifications

CRI	90	
CCT	2700K / 3000K / 3500K / 4000K / 5000K	
Beam angle	110°	
Light Output \pm 3%	2700K: 591 lm	3000K: 607 lm
	3500K: 618 lm	4000K: 625 lm
	5000K: 611 lm	

Mechanical Specifications

IP Rating	Wet locations
Material	Iron + polycarbonate
Lens	Frosted
Net Weight	N/A
Product size (mm)	\pm ϕ 153 x 23.5 mm
Product size (inch)	\pm ϕ 6.02" x 0.93"
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 45°C
Lifespan (L70)	>50 000 hours

Product description:

- Slim LED surface light fixture with 6" overall diameter.
- Installation on junction box.
- Built-in driver. Save space.
- Built-in PIR sensor.
- Delay turning off the light: 1 min / 5 min / 8 min.
- Selectable CCT.
- Can be use as main or decorative lighting.
- Luminaire color: white.

Applications:

Closet, wardrobe, pantry, storage space storage, etc.