



Specifications TLSD7R15AWH

Electrical Specifications

Model No.	TLSD7R15AWH
Power (W) ± 10%	15 W
Input Voltage (V)	AC120 V, 60Hz
Efficacy ± 3%	80 lm/W
Power Factor (PF)	>0.9
Dimmable	Triac

Photometric Specifications

CRI	90
CCT	2700K / 3000K / 3500K / 4000K / 5000K
Beam angle	120°
Light Output ± 3%	2700K: 1186 lm 3000K: 1201 lm
	3500K: 1223 lm 4000K: 1241 lm
	5000K: 1215 lm

Mechanical Specifications

IP Rating	Damp locations
Material	Aluminum + PS
Lens	Frosted
Net Weight	N/A
Product size (mm)	± Ø190 x 20.8 mm
Product size (inch)	± Ø7.48" x 0.82"
Operating Humidity	10% - 90%
Operating Temperature	-25°C ~ 45°C
Lifespan (L70)	>50 000 hours

Product description:

- 7" thin LED surface fixture.
- Built-in driver. Save space.
- Selectable CCT.
- Can be use as main or decorative lighting.
- Luminaire color: white.
- Choice of the frame (color): black or brushed nickel.

Applications:

Offices, shopping malls, schools, hotels, homes, etc.

Optionnal frames

