



Specifications TLSPU50045PBK

Electrical Specifications

| | |
|-------------------|---------------------|
| Model No. | TLSPU50045PBK |
| Power (W) ± 10% | 500 W |
| Input Voltage (V) | AC120-347V, 50/60Hz |
| Efficacy ± 3% | 140 lm/W |
| Power Factor (PF) | 0.9 |

Photometric Specifications

| | |
|-------------------|-----------|
| CRI | 75 |
| CCT | 5 000 K |
| Beam angle | 45° |
| Light Output ± 3% | 70 000 lm |
| Dimmable | 0-10 V |

Mechanical Specifications

| | |
|-----------------------|----------------------|
| IP Rating | IP65 |
| Material | Aluminum |
| Lens | PC |
| Net Weight | 10 kg |
| Product size (mm) | Ø361 x 324 x 409 mm |
| Product size (inch) | Ø14.2 x 12.8 x 16.1" |
| Operating Humidity | 10% - 90% |
| Operating temperature | -40°C ~ 50°C |

Product description:

- Robust and solid, the design provides excellent heat dissipation, ensuring stability and longer life expectancy.
- Available in multiple beam angles for narrow projection.
- Economy on electricity consumption compared to traditional lighting fixture.
- Other CCT available on special request.
- Warranty: 5 years.
- Also available: 15°, 30° and 60°.

Applications:

Flood light.

Stadiums, race track, playgrounds, large area parkings, construction sites, etc.

