



### Specifications TLSPU60045PBK

#### Electrical Specifications

|                      |                     |
|----------------------|---------------------|
| Model No.            | TLSPU60045PBK       |
| Power (W) $\pm 10\%$ | 600 W               |
| Input Voltage (V)    | AC120-347V, 50/60Hz |
| Efficacy $\pm 3\%$   | 140 lm/W            |
| Power Factor (PF)    | 0.9                 |

#### Photometric Specifications

|                        |           |
|------------------------|-----------|
| CRI                    | 75        |
| CCT                    | 5 000 K   |
| Beam angle             | 45°       |
| Light Output $\pm 3\%$ | 84 000 lm |
| Dimmable               | 0-10 V    |

#### Mechanical Specifications

|                       |                      |
|-----------------------|----------------------|
| IP Rating             | IP65                 |
| Material              | Aluminum             |
| Lens                  | PC                   |
| Net Weight            | 10 kg                |
| Product size (mm)     | Ø361 x 324 x 409 mm  |
| Product size (inch)   | Ø14.2 x 12.8 x 16.1" |
| Operating Humidity    | 10% - 90%            |
| Operating Temperature | -40°C ~ 50°C         |

### Product description:

- Robust and solid, the design provides excellent heat dissipation, ensuring stability and longer life expectancy.
- Available in multiple beam angles for narrow projection.
- Economy on electricity consumption compared to traditional lighting fixture.
- Other CCT available on special request.
- Warranty: 5 years.
- Also available: 15°, 30° and 60°.

### Applications:

Flood light.

Stadiums, race track, playgrounds, large area parkings, construction sites, etc.

