



## Specifications TLSPU72030PBK

### Electrical Specifications

Model No.	TLSPU72030PBK
Power (W) $\pm 10\%$	720 W
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy $\pm 3\%$	140 lm/W
Power Factor (PF)	0.9
Surge protection	10 kv
Total harmonic distortion	N/A

### Photometric Specifications

CRI	75
CCT	5 000 K
Beam angle	30°
Light Output $\pm 3\%$	100 800 lm
Dimmable	0-10 V

### Mechanical Specifications

IP Rating	IP65
Vibration rating	3G
EPA	1.97 pi <sup>2</sup>
Material	Aluminum
Lens	PC
Net Weight	15 kg
Product size (mm)	Ø463 x 378 x 568 mm
Product size (inch)	Ø18.2 x 18.2 x 22.4"
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C



## Product description:

- Robust and solid, the design provides excellent heat dissipation, ensuring stability and longer life expectancy.
- Available in multiple beam angles for narrow projection.
- Economy on electricity consumption compared to traditional lighting fixture.
- Other CCT available on special request.
- Warranty: 5 years.
- Also available: 15°, 45° and 60°.

## Applications:

Flood light.

Stadiums, race track, playgrounds, large area parkings, construction sites, etc.

### Accessories not included



**TLSPSFBK**  
Laser aiming device



**TLSPHAD**  
«Slip fitter» bracket