



Specifications TLTDL4R9AWH

Electrical Specifications

| | |
|-------------------|---------------|
| Model No. | TLTDL4R9AWH |
| Power (W) ± 10% | 9 W |
| Input Voltage (V) | AC120 V, 60Hz |
| Efficacy ± 3% | 78 lm/W |
| Power Factor (PF) | >0.9 |
| Dimmable | Triac |

Photometric Specifications

| | |
|-------------------|------------|
| CRI | >80 |
| CCT | Selectable |
| Beam angle | 120° |
| Light Output ± 3% | 700 lm |

Mechanical Specifications

| | |
|-----------------------|-------------------------|
| IP Rating | IP20 |
| Material | Aluminum + Steel box |
| Lens | Frosted (polycarbonate) |
| Net Weight | 276 g |
| Product size (mm) | ± Ø123 x 22 mm |
| Product size (inch) | ± Ø4.8" x 0.87" |
| Operating Humidity | 10% - 90% |
| Operating Temperature | -20°C~45°C |
| Lifespan (L70) | N/D |

Product description:

- Ultra thin 4" recessed down light.
- Type IC.
- Airtight.
- Junction box with quick connector included.
- 5 CCT: selectable 2 700 K, 3 000 K, 3 500 K, 4 000 K and 5 000 K using a switch.
- Color: white.
- Optional installation plate.

Applications:

Houses, schools, shopping centers, etc.

Optional installation plates and fixing bars

