

## Specifications TLTFUS24W50AD

### Electrical specifications

Model No.	TLTFUS24W50AD
DLC ID	S-W7U69D
Adjustable power (W) ± 10%	30W / 40W / 50W
Input Voltage (V)	AC 120/347V, 50/60Hz
Efficacy ± 3%	126.26 lm/W
Power Factor (PF)	0.952
Surge protection	N/A
Total harmonic distortion	12.6 %

### Photometric specifications

CRI	82	
Selectable CCT	3500K / 4000K / 5000K	
Beam angle	120°	
Light Output ± 3%	30W: 3788 lm	40W: 5050 lm
	50W: 6313 lm	
Dimmable	0-10V	

### Mechanical specifications

IP Rating	IP20
Material	SPCC + PC
Lens	Frosted
Net Weight	7 kg
Product size (mm)	± 1213 x 603 x 50 mm
Product size (inch)	± 48 x 24 x 2 in
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C
Lifespan (L70)	54 000 hours



## Product description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Versatile design makes installation easy which reduces installation time and costs.
- Saves on electricity consumption compared to fluorescent lighting fixture.
- Warranty: 5 years.
- High efficiency reflective PC cover, soft and bright lighting.

## Applications:

Suitable for offices, conference rooms, shops, supermarkets, etc.

### Optional accessories

		
Surface insallation frame 2' x 4' white	Recessed mounting frame 2' x 4' white	Emergency battery
TLPL24WMF	TLPL24RMFWH	BLD-HM15D

[info@technilight.ca](mailto:info@technilight.ca)

[WWW.TECHNILIGHT.CA](http://WWW.TECHNILIGHT.CA)