



### Specifications TLTL20D36ABK

#### Electrical Specifications

Model No.	TLTL20D36ABK
DLC ID	N/D
Power (W) ±10%	20W
Input Voltage (V)	AC 120V, 50/60Hz
Efficacy ± 3%	100 lm/W
Power Factor (PF)	0.9
Surge protection	N/D
Total harmonic distortion	<20%
Dimmable	Triac

#### Photometric Specifications

CRI	>90
CCT selectable	27K / 30K / 35K / 40K / 50K
Beam angle	36°
Light Output ± 3%	2 000 lm

#### Mechanical Specifications

IP Rating	N/D
Matériau	Aluminum + PMMA
Lens	Clear
Net Weight	0.8 kg
Product size (mm)	± Ø85 x 258.7 mm
Product size (inch)	± Ø3.4" x 10.2"
Operating Humidity	10% to 90%
Operating Temperature	-20°C to 45°C
Lumen maintenance	N/A

#### Accessories (not included)

 TLTL15/20/25L24	24° lens for track light	 TLTL15/20/25L60	60° lens for track light	 PRO-0310A-B	3 wires single phase, 1 m HALO track
 PRO-0315A-B	3 wires single phase, 1.5 m HALO track	 PRO-0320A-B	3 wires single phase, 2 m HALO track	 PRO-0331-B	Live end connector for 3 wires HALO track
 PRO-0333-B	Joint for 3 wires HALO track	 PRO-0334-B	Straight connector for 3 wires HALO track	 PRO-0335-B	L connector for 3 wires HALO track
 PRO-0336-B	T connector for 3 wires HALO track	 PRO-0337-B	X connector for 3 wires HALO track	 PRO-0341-B	Junction box connector for 3 wires HALO track
 PRO-0342-B	4" cover, use with PRO-0331-B				

#### Product description:

- Selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K.
- Adjustable 350° horizontal and 90° vertical rotation.
- Interchangeable projection angle: 24° / 36° / 60°.
- Energy savings compared with conventional lighting.
- Warranty: 5 years.
- Compatible with HALO 3 single-circuit rail system connections.
- Color: black.

#### Applications:

Suitable for offices, sales areas, residential lighting, art galleries, museums, halls, etc.