



Specifications TLTL30N2050AWH

Electrical Specifications

Model No.	TLTL30N2050AWH
DLC ID	N/A
Power (W) ±10%	20W / 25W / 30W
Input Voltage (V)	AC 120V, 50/60Hz
Efficacy ± 3%	90 lm/W
Power Factor (PF)	0.9
Surge protection	N/A
Total harmonic distortion	N/A
Dimmable	No

Photometric Specifications

CRI	>90
CCT selectable	2700K / 3000K / 3500K / 4000K / 5000K
Beam angle	20° - 50°
Light Output ± 3%	20W: 1 800 lm 25W: 2 250 lm 30W: 2 700 lm

Mechanical Specifications

IP Rating	N/A
Matériau	Aluminum
Lens	Clear
Net Weight	0.85 kg
Product size (mm)	± Ø85.1 x 175 mm
Product size (inch)	± Ø3.35" x 6.89"
Operating Humidity	10% ~ 90%
Operating Temperature	-20°C ~ 45°C
Lumen maintenance	N/A

Accessories (not included)

	3 wires single phase, 2' HALO track		3 wires single phase, 4' HALO track		3 wires single phase, 6' HALO track
	3 wires single phase, 8' HALO track		Live end connector for 3 wires HALO track		Joint for 3 wires HALO track
	Straight connector for 3 wires HALO track		L connector for 3 wires HALO track		T connector for 3 wires HALO track
	X connector for 3 wires HALO track		Junction box connector for 3 wires HALO track		4" cover, use with PRO-0331-B

Product description:

- UGR: <19.
- Adjustable 350° horizontal and 180° vertical rotation.
- Adjustable beam angle: from 20° to 50°.
- Energy savings compared with conventional lighting.
- Warranty: 5 years.
- Compatible with HALO and JUNO rail systems.
- Color: white.

Applications:

Suitable for offices, sales areas, residential lighting, art galleries, museums, halls, etc.