

### Electrical specifications

|                           |              |
|---------------------------|--------------|
| Model no.                 | TLTLAL45AWH  |
| DLC ID                    | -            |
| Power $\pm 10\%$          | 45W          |
| Input voltage             | AC120V       |
| Frequency                 | 60 Hz        |
| Efficacy $\pm 3\%$        | 70 lm/W      |
| Power factor              | >0.5         |
| Dimmable                  | Triac        |
| Surge protection          | 2 kv         |
| Total harmonic distortion | $\leq 140\%$ |

### Photometric specifications

|                        |                                       |
|------------------------|---------------------------------------|
| CRI                    | 90                                    |
| CCT                    | 2700K / 3000K / 3500K / 4000K / 5000K |
| Beam angle             | 100°                                  |
| Light output $\pm 3\%$ | 3 150 lm                              |

### Mechanical specifications

|                       |                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------|
| IP rating             | IP20 / Damp locations                                                               |
| Material              | Aluminum alloy                                                                      |
| Lens                  | Polycarbonate                                                                       |
| Net weight            | 9.1 kg                                                                              |
| Product dimensions    | $\pm 50'' \times 1.30'' \times 1.97''$<br>$\pm 1270 \times 33 \times 50 \text{ mm}$ |
| Operating humidity    | 40% ~ 60%                                                                           |
| Operating temperature | -25°C ~ 50°C                                                                        |
| Lumen maintenance     | -                                                                                   |


### Product description:

- Selectable CCT.
- Vertical rotation of the luminaire up to 45°.
- Halo adapter: single-phase 3-wire.

### Applications:

Indoor track lighting fixture.

### Optional accessories

|                                                                                     |                                                                                       |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |
| <b>PRO-0302A-W</b>                                                                  | <b>PRO-0304A-W</b>                                                                    | <b>PRO-0306A-W</b>                                                                    | <b>PRO-0308A-W</b>                                                                    |
| 3 wires single phase, 2' HALO track                                                 | 3 wires single phase, 4' HALO track                                                   | 3 wires single phase, 6' HALO track                                                   | 3 wires single phase, 8' HALO track                                                   |
|  |  |  |  |
| <b>PRO-0331-W</b>                                                                   | <b>PRO-0333-W</b>                                                                     | <b>PRO-0334-W</b>                                                                     | <b>PRO-0335-W</b>                                                                     |
| Live end connector for 3 wires HALO track                                           | Joint for 3 wires HALO track                                                          | Straight connector for 3 wires HALO track                                             | L connector for 3 wires HALO track                                                    |
|  |  |  |  |
| <b>PRO-0336-W</b>                                                                   | <b>PRO-0337-W</b>                                                                     | <b>PRO-0341-W</b>                                                                     | <b>PRO-0342-W</b>                                                                     |
| T connector for 3 wires HALO track                                                  | X connector for 3 wires HALO track                                                    | Junction box connector for 3 wires HALO track                                         | 4" cover, use with PRO-0331-W                                                         |