




# TLTS30F5N

# IP20

## Rigid LED strip



### Specifications TLTS30F5N

#### Electrical Specifications

Model No.	TLTS30F5N
Power (W) ± 10%	5 W
Input Voltage (V)	DC 24V
Efficacy ± 3%	70 lm/W
Power Factor (PF)	0.9

#### Photometric Specifications

CRI	>80
CCT	4 000 K
Beam angle	100°
Light Output ± 3%	350 lm
Dimmable	No

#### Mechanical Specifications

IP Rating	IP20
Material	Aluminum + polycarbonate
Lens	Frosted
Net Weight	0.7 kg
Product size (mm)	± 300 x 18 x 8 mm
Product size (inch)	± 11.81" x 0.71" x 0.31"
Operating Humidity	10% - 90%
Operating Temperature	0°C ~ 45°C
Lumen maintenance	N/A

### Product description:

- Soft, uniform lighting.
- Quick connection between LED bars.
- Saves energy compared to conventional lighting.
- Warranty: 5 years.
- Other CCT available on request.
- Several installation methods.

### Applications:

Suitable for counters, displays, etc.

### Accessories:

**XY36S2401500QUF** 120VAC / 24VDC 36W power supply

**TLTS24PC** 24" power cable

**TLTS120PC** 120" power cable

**TLTSMC21** Interconnection block

**TLTS24IC** 24" interconnection cable

[info@technilight.ca](mailto:info@technilight.ca)

[WWW.TECHNILIGHT.CA](http://WWW.TECHNILIGHT.CA)