




TLTS60F9N

IP20

Rigid LED strip



Specifications TLTS60F9N

Electrical Specifications

| | |
|-------------------|-----------|
| Model No. | TLTS60F9N |
| Power (W) ± 10% | 9 W |
| Input Voltage (V) | DC 24V |
| Efficacy ± 3% | 70 lm/W |
| Power Factor (PF) | 0.9 |

Photometric Specifications

| | |
|-------------------|---------|
| CRI | >80 |
| CCT | 4 000 K |
| Beam angle | 100° |
| Light Output ± 3% | 630 lm |
| Dimmable | No |

Mechanical Specifications

| | |
|-----------------------|--------------------------|
| IP Rating | IP20 |
| Material | Aluminum + polycarbonate |
| Lens | Frosted |
| Net Weight | 0.14 kg |
| Product size (mm) | ± 600 x 18 x 8 mm |
| Product size (inch) | ± 23.6" x 0.71" x 0.31" |
| Operating Humidity | 10% - 90% |
| Operating Temperature | 0°C ~ 45°C |
| Lumen maintenance | N/A |

Product description:

- Soft, uniform lighting.
- Quick connection between LED bars.
- Saves energy compared to conventional lighting.
- Warranty: 5 years.
- Other CCT available on request.
- Several installation methods.

Applications:

Suitable for counters, displays, etc.

Accessories:

XY36S2401500QUF 120VAC / 24VDC 36W power supply

TLTS24PC 24" power cable

TLTS120PC 120" power cable

TLTSMC21 Interconnection block

TLTS24IC 24" interconnection cable

info@technilight.ca

WWW.TECHNILIGHT.CA